TECHNICAL SPECIFICATION :

Contact Material	Silver Alloy
Contacts	SPDT (1 form C)
Contact Rating	10 AMPS (5 Amps optional) resistive at 240 V AC/24V DC
Initial Contact Resistance	0.100 Ohms (max.)
Ambient Temperature	-20°C to +70°C
Di-electric Strength	1.5 KV coil to contacts 750 VAC across open contacts
Insulation Resistant	100 Meg-Ohms min at 500 VDC AT 65% RH
Operate Time	0.010 sec.max. at nominal Voltage
Release Time	0.005 sec.max. at nominal Voltage
Life expectancy	10^5 operations at rated load
Max. Weight	10 gms



COIL-DATA

(All Values at 27°C±2°C Ambient)

Nominal Voltage	Resistance in Ohms±10%	Must Operate Voltage	Must Release Voltage
12VDC	400	9	1.2
24VDC	1600	18	2.4

Note : For Non-standard coil voltage or resistance, Please contact.

CAT .NO: SCR/0601

SALIENT FEATURES

- SUBMMIATURE
- PCB MOUNTABLE
- HIGH CAPACITY

APPLICATIONS:-

- UPS
- Stabilizers
- Timers
- Temp. controllers
- Pressure controllers
- PC Add ON cards
- Instrumentation



MADHU SUBTRONIC COMPONENTS PVT.LTD
Off : 1 st Floor, Krishna Bldg, Shamrao Vithal Lane,
Off. Lamington Rd, Mumbai – 400 007
Tel : - 91 2380 0783 / 2386 4484 / 2387 6707, Fax : - 91 22 2387 6729
email : - mscpl@vsnl.com Website : - www.mscpl.com